

∞ Infinity ACL M



KEY FEATURES

- • **“MULTI-lamp”** concept ready
- **Extreme output** equalling a 2k lamp! in a 250 W package
- **Variable beam control with rotating aerial effects**
- **Wash «frosted» look**
- **Focusable black-light**
- **Included moon flower effect**
- **Split color beam effects**
- **Cinema effect**

SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- CTO filter
- UV effect
- 7 rotating aerial effects + open
- Film frame effect
- Proportional variable beam angle
- Min/Max beam angle 3°/ 7°
- Proportional frost
- Proportional iris
- Dimmer
- Mechanical and electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

PHYSICAL SIZE

- Length: 459 mm (18.1 in)
- Width: 377 mm (14.8 in)
- Height: 612 mm (24.1 in), head straight up
- Weight: 23 kg (50.7 lbs)

LAMP AND BALLAST

- Type: Philips MSR Gold 700/2 Mini FastFit, MULTI-lamp ready
- Socket: PGJX28
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Artnet
- DMX channels: 20
- Setting and addressing: LCD display or via DR 1 + (allows replication of all display functions remotely via bidirectional DMX 512 and software upgrades)

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90 – 260 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: max 700W= 4,5 A at 230 V, 9,5 A at 115 V
cos ϕ = 0,9
- DMX data in/out: 3 pin and 5 pin locking XLR
- Ethernet RJ45 port